



ACRYLIFE® 1500 Roofing System

1165 Stafford Umberger Drive ♦ Wytheville, Virginia 24382

♦ 276-228-6704 ♦ 800-253-3597 ♦ Fax 276-228-3331

ACRYLIFE SYSTEM DATA

Product Name:

ACRYLIFE® 1500 System for recovery of Single ply membranes (EPDM, Hypalon, PVC...)

Manufacturer

Acrylife, Inc.

P.O. Box 803

1165 Stafford Umberger Drive

Fairview Industrial Park

Wytheville, Va. 24382

Phone: (800) 253-3597

Fax: (276) 228-3331

Website: www.acrylife.com

E-mail: info@acrylife.com

System Description

The Acrylife 1500 system is a fabric reinforced membrane roof system. The system is designed to provide an economical solution to maintain and recover deteriorated single ply membrane roofs. The system provides a recovery process that will insure a watertight membrane over the existing single ply with renewed flexibility and longevity. The design technology introduces a flexible membrane that is chemically resistant, safe to install, environmentally friendly with the added value benefit of being renewable.

Product Description

Acrylife Acrylic is specially formulated, premium grade Acrylic elastomer. ACRYLIFE® Acrylic contains UV and thermal stabilizers, biocides, and other ingredients to keep the acrylic flexible and weather resistant. The acrylic may be applied with conventional spray equipment, roller or brush. ACRYLIFE® Acrylic is an elastomeric used as a base and finish coat system. The acrylic has excellent adhesion characteristics to properly prepared membrane surfaces. The system offers easy installation, excellent weatherability, fast drying and a pleasing appearance.

Product Yield

24 dry mils of Acrylic required and applied in two coats.

One square (100 square feet) of coverage requires 2.5 gallons of Acrylic.

Allowance: Allow 10 – 15% additional materials for irregular surfaces.

Technical Data:

ACRYLIFE Acrylic

<u>TEST</u>	<u>METHOD</u>	<u>RESULTS</u>
Elongation	ASTM D-412	> 250 %

Tensile Strength	ASTM D-412	> 100 psi
------------------	------------	-----------

Water Resistance	ASTM E – 96	< 0.2 perms/hr.
------------------	-------------	-----------------

Percent Solids	Weight	67%
----------------	--------	-----

Cold Crack	180°	-30° F
------------	------	--------

Storage Temp.		40 – 100° F
---------------	--	-------------

Ordering Information

<u>Container Size</u>	<u>Weight</u>
5-Gallon Pail	62 Pounds
55 Gallon Drums	745 Pounds

Warranty

Acrylife will warranty the system on approved applications for a period of 10 years from the time of completion. Acrylife, Inc. will repair or cause to be repaired leaks which are a result of materials or workmanship supplied by Acrylife subject to the cost of the original installation.

Technical Services

Acrylife, Inc. provides technical manuals, detailed drawings, specifications and installation guides to architects, engineers, specifiers and contractors. Contractors are trained and certified as dealer installers and all projects are inspected by a technical service representative before a warranty is issued. Contact Acrylife at (800) 253-3597 for technical support.